

TECHNICAL DATA



PURE WHITE

BLOCKOUT

Standard

Unit

650 PURE WHITE

750 PURE WHITE

850 PURE WHITE

950 PURE WHITE

1050 PURE WHITE

750 BLOCKOUT

850 BLOCKOUT

MATERIAL COMPOSITION

Base Fabric						Polyester				
Coating						PVC Coated				
Lacquering						PVDF				

TECHNICAL SPECIFICATION

Weight	DIN EN ISO 2286-2	gsm	650	750	850	950	1050	750	850
Thickness	ISO 4593	mm	0.52	0.6	0.65	0.75	0.82	0.6	0.65
Adhesion	EN ISO 2411	N/5 cm	>100			>120		>100	
Translucency	SIJIA LAB STANDARD	%	4-10%					0%	

PERFORMANCE PROPERTIES

Flex Resistance	DIN 53359A	100,000					100,000		
Tear Resistance	DIN 53363	N/5 cm	300/250	350/300	500/450	550/500	350/300		
Temperature Resistance	DIN EN 1876-1	°C	-30°C-70°C						
Tensile Strength	EN ISO 1421	N/5 cm	2800/2500	3000/2800	4000/3500	4600/4500	3000/2800		
Flame Resistance	DINA 4102 EN13501	B1							
Light Fastness	ISO 4802-3-2006	>6							